



Product technical sheet

WOODEN WD1405







3 - 14 years

13 kids

26,4 m²



Material specification

- The structure is made of a durable, moisture-resistant and low-temperature recycled composite,
- Platforms and climbing walls made of durable anti-slip and waterproof plywood or HPL plate,
- Structure for platforms made of hot-dip galvanized and powder coated steel;
- Roofs and side palels made of recycled HDPE boards, resistant to weather conditions.
- Slides made of stainless steel with sides made of recycled HDPE boards, resistant to amospheric conditions,
- Fireman's pole made of stainless steel,
- Climbing stones made of recycled HDPE plate, resistant to weather conditions,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- · Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps made of polypropylene,



Facilitating disability



easy access



integration



Physical development



sliding



pull-up



passage



climbing










Product technical sheet


WOODEN WD1405






4 number of activity elements







Product data

Length	328 cm	
Width	245 cm	
Total height	337 cm	
Age group	3 - 14 years	
Number of users	13 kids	
Safety zone	26,4 m2	
Free fall height	150 cm	
The height of the platforms	150 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	40 kg	
Dimensions of the largest part	365x9x9 cm	
Availability of spare parts	YES	
Installation time	4,5 h	
Color options		

Data is subject to change without prior notice.

Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com



Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C) Particle size from 20 to 80	30	≤200	
	40	≤300	
woodchips (A,C) Particle size from 5 to 30	30	≤200	
	40	≤300	
sand or gravel (A,C) Particle size from 0,25 to 8	30	≤200	
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		150

Product technical sheet

WOODEN WD1405

Amount of safe surface corresponding with free fall height:

HIC 100	5,7 m ²
HIC 150	20,7 m ²

Data is subject to change without prior notice.

