



Product technical sheet

WOODEN WD1504







3 - 14 years

29 kids

43,4 m²



Material specification

- Construction made of the highest quality laminated, impregnated and double coated pine wood 90 x 90 mm without knots, secured from the top with polypropylene plugs,
- Metal anchors made of hot dip galvanized steel, protecting the wood from direct contact with the ground to prevent rot and to extend the product's life,
- Platforms and steps made of durable anti-slip and waterproof plywood or HPL plate,
- Structure for platforms made of hot-dip galvanized and powder coated steel;
- Roofs, side panels made of durable HDPE or HPL plate, resistant to weather conditions,
- Slides made of stainless steel with durable HDPE or HPL side panels,
- Educational paneles and moving elements made of HDPE or HPL plate, resistant to weather conditions,
- · Windows and/or elements made of polycarbonate,
- Maze windows made of polycarbonate, balls made of synthetic material,
- Stainless steel bars and handrails,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps made of polypropylene,



Facilitating disability



easy access



shelters



Intellectual development



manipulation



music



sight





Physical development



sliding

06/10/2022











Product technical sheet WOODEN WD1504

Product data

Length	440 cm	
Width	451 cm	
Total height	367 cm	
Age group	3 - 14 years	
Number of users	29 kids	
Safety zone	43,4 m2	
Free fall height	180 cm	
The height of the platforms	35,120, 150, 180 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	34 kg	
Dimensions of the largest part	317x9x9 cm	
Availability of spare parts	YES	
Installation time	9 h	
Color options		


Data is subject to change without prior notice.


Additional information


- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

8 number of interactive elements









Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		180

Product technical sheet

WOODEN WD1504

Amount of safe surface corresponding with free fall height:

HIC <60	0,5 m ²
HIC 100	9,4 m²
HIC 120	10,6 m ²
HIC 150	6,4 m ²
HIC 180	16,5 m²

Data is subject to change without prior notice.

